

# Data Sheet

## HS STRAWBERRY SYSTEM



### Properties

#### Material - Gutter

100% polypropylene copolymer 1st quality, UV protection

#### Maximum load - Spacer

20 Kg/m uniformly

#### Disinfection of the gutter

It is recommended:

- Sodium Hypochlorite (NaClO) concentration 200 ppm, clearing up afterwards with water
- Hydrogen Peroxide (H<sub>2</sub>O<sub>2</sub>)

#### 110135 | GUTTER 135x135x0,7mm



Polypropylene  
Weight: 178 g/m<sup>2</sup>

#### 020002 | SPACER 1000x235mm



Polypropylene  
Pésigfű76 76 g

#### 030005 | CLIP 50x30.6mm



Polypropylene  
Pésigfű76 g

#### 040003 | OUT-FLOW 111x235x165mm




Polypropylene  
Pésigfű76 32 g

#### 040004 | CAP 100x235x60mm



Polypropylene  
Pésigfű76 6 g

#### ● 990001 | LATTICE 220x140mm ● 990002 | LACQUER LATTICE 220x140mm




Poliipropileno  
Pésigfű76 5 Kg/m

#### 050001 | STEM 1"



Polypropylene  
Weight: 22 g

#### 050002 | NUT 1"



Poliipropileno  
Pésigfű76 4 g

#### 050003 | RUBBER WASHER 1"



Rubiipropileno  
Pésigfű76 g

#### 960006 | POST 32x2.5x1400mm



Galvanised steel  
Weight: 3 Kg

#### 970005 | SUPPORT 264x195mm



Galvanised steel  
Weight: 205 g